

High-speed PCIe cameras

ximea

fastest image transfer • high resolution • no frame grabber required



xiB

housed cameras with PCIe interface

xiB - series camera specifications

xiB is a compact camera using the most recent high resolution CMOS sensors with outstanding features:

- PCIe x4 Gen2 interface for direct access to and from the computer memory with up to 20 Gbit / sec
- No frame grabber required
- Most recent high resolution CMOSIS sensors
- Robust PCIe and Power/GPIO connectors, slim design
- Integrated Canon EF lens interface for control of dynamic aperture and focus.
- Windows and Linux support with DMA (direct memory access) image data transfer
- Compact housing: 60 x 60 x 38 mm

Sensors and models:

Model ¹⁾	Sensor	Resolution	Pixel size [um]	ADC [bits]	DR [dB]	FWC [e-]	Diagonal [mm]	Power [W]	FPS ²⁾
CB120xG-CM	CMOSIS CMV12000	4096 x 3072, 12 MP	5.5	8,10,12	60	13500	28	6.5	100
CB200xG-CM	CMOSIS CMV20000	5120 x 3840, 20 MP	6.4	12	66	15000	41	6	32

Note 1: various models available: x = C for color, M for monochrome

Note 2: RAW, 12 bit, full resolution

Compatibility:

Standard **Windows and Linux** operation systems • GenICam / GenTL • Single SDK/API for all XIMEA camera models. Compatible with the widest range of vision libraries. Please check website for up-to-date list!



All trademarks are the property of their respective holders, used with permission. All other rights reserved.

Contact:

Please visit ximea.com for complete product information.

E-mail our sales team at sales@ximea.com for your price and further information.

	XIMEA GmbH, Germany Hansestraße 81 48165 Münster Germany info@ximea.com Tel: +49 2501 964 555-0 Fax: +49 2501 964 555-99	XIMEA s.r.o., Slovakia Lesna 52 900 33 Marianka Slovakia info@ximea.com Tel: +421 (2) 205 104 26 Fax: +421 (2) 205 104 27	XIMEA Corp., USA 2102 Beech Court Golden, CO 80401 USA info@ximea.com Tel: +1 (303) 389-9838 Fax: +1 (303) 202-6350
---	---	--	--