

USB3 High-end CCD camera series

ximea

single board design • USB3.0 bus powered • fastest multi-tap readout



xiD

board level and housed cameras

xiD - series camera specifications

xiD is an ultra-compact USB3.0 camera family using the most recent CCD sensors for industrial and scientific purposes with outstanding features:

- ultra-low read-out noise, clear 14 bits/pixel images in all modes
- partial readout and several binning modes with enhanced sensitivity and highest frame rates
- board level cameras available

Sensors and models:

Model ¹⁾	Sensor	Resolution	Pixel size [µm]	ADC [bits]	DR [dB] ²⁾	FWC [e-]	Sensor size [mm]	Diagonal [mm]	Power [W]	FPS ³⁾
MD028xU-SY	SONY ICX674	1934 x 1456, 2.8 MP	4.54	8,10,12,14	71.1	20000	8.8 x 6.6	11	3.6 W	56.9
MD061xU-SY	SONY ICX694	2754 x 2204, 6.1 MP	4.54	8,10,12,14	71.8	19500	12.5 x 10.0	16	3.9 W	28.4
MD091xU-SY	SONY ICX814	3384 x 2708, 9.1 MP	3.69	8,10,12,14	68.4	12000	12.5 x 10.0	16	4.2 W	19.5
MD120xU-SY	SONY ICX834	4242 x 2830, 12.0 MP	3.1	8,10,12,14	63.1	10000	13.2 x 8.8	15.8	4.5 W	15.3

Note 1: various models available: x = C color, M mono

Note 2: 26 MHz readout frequency

Note 3: 52 MHz, 4 taps, RAW14 bits; + 20% in overlocked mode, 12bit packed

- Sony “EXview HAD CCD II” pixel technology with improved light efficiency for the near-infrared spectrum
- XIMEA’s proprietary CLEANPATH - readout and sensor driving circuitry, enabling scientific imaging with extremely low readout noise and high fidelity in color reproduction.
- Global shutter CCD with interline transfer - 1, 2 or 4 tap readout with 14 bit ADC
- No selected grades - all cameras are scientific grade

Compatibility:

Standard **Windows, Linux & MacOS** operation systems • USB3.0 • GenICam / GenTL • Single SDK/API for all XIMEA camera models. Compatible with the widest range of vision libraries. Please check website for up-to-date list!



All trademarks are the property of their respective holders, used with permission. All other rights reserved.

Contact:

Please visit ximea.com for complete product information.

E-mail our sales team at sales@ximea.com for your price and further information.

	XIMEA GmbH, Germany Hansestraße 81 48165 Münster Germany info@ximea.com Tel: +49 2501 964 555-0 Fax: +49 2501 964 555-99	XIMEA s.r.o., Slovakia Lesna 52 900 33 Marianka Slovakia info@ximea.com Tel: +421 (2) 205 104 26 Fax: +421 (2) 205 104 27	XIMEA Corp., USA 2102 Beech Court Golden, CO 80401 USA info@ximea.com Tel: +1 (303) 389-9838 Fax: +1 (303) 202-6350
---	---	--	--